


Sensor-switched outdoor light

L 830 LED iHF

Silver

EAN 4007841 055509

STEINEL[®]
Intelligent technology



LED

30 years (Ø 4,5h / day)



3000K warm-white



intelligent high frequency sensor
160°



1 - 5 m



IP44



2 - 2000 lux



5 sec - 60 min



soft light start



manual override



energy saving

Function description

Digital. Interconnected. Intelligent. The L 830/835/840 LED iHF range of sensor-switched lights captivates with a classy look and embellishes any building. With concealed 160° iHF sensor (5 m reach) that only responds to human movement. Night-light function, soft light start and 4-hour manual override (3000 K). Wireless interconnection via Bluetooth, any chosen settings via STEINEL app. Three design options. Available in anthracite or silver.

Sensor-switched outdoor light

L 830 LED iHF

Silver

EAN 4007841 055509


STEINEL[®]
Intelligent technology

Technical specifications

| | |
|---|---|
| Dimensions (L x W x H) | 110 x 110 x 132 mm |
| Mains power supply | 220 – 240 V / 50 – 60 Hz |
| Mounting height max. | 2,50 m |
| Sensor Technology | iHF (intelligent high-frequency technology) |
| Output | 9,5 W |
| Interconnection | Yes |
| Type of interconnection | Master/slave |
| Luminous flux | 608 lm |
| Colour temperature | 3000 K |
| Colour Rendering Index CRI | 80-89 |
| With lamp | Yes, STEINEL LED system |
| Lamp | LED cannot be replaced |
| LED life expectancy (max. °C) | 50000 h |
| Base | without |
| LED cooling system | Passive Thermo Control |
| With motion detector | Yes |
| Detection angle | 160 ° |
| Angle of aperture | 160 ° |
| Sneak-by guard | Yes |
| Capability of masking out individual segments | Yes |
| Electronic scalability | Yes |


| | |
|---------------------------------|------------------------------|
| Mechanical scalability | No |
| Reach, radial | r = 5 m (35 m ²) |
| Photo-cell controller | Yes |
| Twilight setting | 2 – 2000 lx |
| Time setting | 5 s – 15 Min. |
| Basic light level function | Yes |
| Basic light level function time | 10/30 min, all night |
| Soft light start | Yes |
| Continuous light | selectable, 4h |
| Impact resistance | IK03 |
| IP-rating | IP44 |
| Protection class | II |
| Ambient temperature | -20 – 40 °C |
| Housing material | Plastic |
| Cover material | Plastic, opal |
| Manufacturer's Warranty | 3 years |
| Settings via | Bluetooth, Potentiometers |
| With remote control | No |
| Version | Silver |
| PU1, EAN | 4007841055509 |

Detection Zone



Mögliche Montagehöhe: 1,80 m – 2,50 m
Orange: radial und tangential

Dimension Drawing



Sensor-switched outdoor light


L 830 LED iHF

Silver

EAN 4007841 055509



Master/slave interconnection circuit diagram



Master/master interconnection circuit diagram

